


DME430

DIA-MAX 스퀘어 엔드밀 4날 헬릭스30°

DIA-MAX Square End Mill 4-Flute Helix30°



CARBIDE
Fine

DIA
CVD

4

30°
Helix

D
0/-0.02

Shank
h5

D≥1

* 적용 피삭재 (Applicable Work Material)
◎ : 최적 (Most Suitable)
○ : 가능 (Applicable)

P			H			M	S	N		
탄소강 Carbon Steels	합금강 Alloy Steels	프리하든강 Pre-Hardened Steels	열처리강 Hardened Steels			스테인레스강 Stainless Steels	내열합금강 Heat-resistant alloys	동 Copper	알루미늄합금 Alumium Alloys	흑연 Graphite
S45C/S50C ~800 N/mm²	SCM ~35HRC	NAK/HPM ~45HRC	SKD61 ~55HRC	SKD11 ~60HRC	SKH ~62HRC					
								○		◎

단위(mm)/Unit(mm)


모델번호 Model No.	인선직경 Dia of Mill	날장 Length of Cut	전장 Overall Length	생크경 Shank Dia	비고 Remark
	D	l ₁	L	d	
DME430-01003-050-S04	1	3	50	4	
DME430-01504-050-S04	1.5	4	50	4	
DME430-02006-050-S04	2	6	50	4	
DME430-03012-060-S06	3	12	60	6	
DME430-04016-060-S06	4	16	60	6	
DME430-05020-070-S06	5	20	70	6	
DME430-06020-070-S06	6	20	70	6	
DME430-08024-070-S08	8	24	70	8	
DME430-10025-080-S10	10	25	80	10	
DME430-12025-080-S12	12	25	80	12	

DIA-MAX
볼
Ball
래디우스
Radius
스퀘어
Square

CHC200

면취 커터 2날 헬릭스0°

Chamfer Cutter 2-Flute Helix 0°



CARBIDE
ULTRA

TiSiN

2

0°
Helix

Shank
h5

C

* 적용 피삭재 (Applicable Work Material)
◎ : 최적 (Most Suitable)
○ : 가능 (Applicable)

P			H			M	S	N		
탄소강 Carbon Steels	합금강 Alloy Steels	프리하든강 Pre-Hardened Steels	열처리강 Hardened Steels			스테인레스강 Stainless Steels	내열합금강 Heat-resistant alloys	동 Copper	알루미늄합금 Alumium Alloys	흑연 Graphite
S45C/S50C ~800 N/mm²	SCM ~35HRC	NAK/HPM ~45HRC	SKD61 ~55HRC	SKD11 ~60HRC	SKH ~62HRC					
◎	◎	◎	○			○	○	○	○	○

단위(mm)/Unit(mm)

모델번호 Model No.		선단경 Front Dia	각도(편각) Taper Angle on Side	날장 Length of Cut	전장 Overall Length	생크경 Shank Dia	비고 Remark
비코팅 Uncoated	코팅 Coated	D ₁	θ	l ₁	L	d	
CHC200-000T300-050-S04	HMCHC200-000T300-050-S04	0	30°	3.4	50	4	
CHC200-000T450-050-S04	HMCHC200-000T450-050-S04	0	45°	2	50	4	
CHC200-000T600-050-S04	HMCHC200-000T600-050-S04	0	60°	1.15	50	4	
CHC200-000T300-060-S06	HMCHC200-000T300-060-S06	0	30°	5.1	60	6	
CHC200-000T450-060-S06	HMCHC200-000T450-060-S06	0	45°	3	60	6	
CHC200-000T600-060-S06	HMCHC200-000T600-060-S06	0	60°	1.73	60	6	
CHC200-000T450-065-S08	HMCHC200-000T450-065-S08	0	45°	4	65	8	
CHC200-000T450-070-S10	HMCHC200-000T450-070-S10	0	45°	5	70	10	
CHC200-000T450-075-S12	HMCHC200-000T450-075-S12	0	45°	6	75	12	
CHC200-000T450-110-S12	HMCHC200-000T450-110-S12	0	45°	6	110	12	

FORMED TOOL